



# Serie SC per conservazione campioni

## Liquid nitrogen storage SC Series



La serie SC è stata ideata per l'utente che ha ridotte esigenze di capacità per lo stoccaggio di campioni, ma che necessita di una conservazione a lungo termine e con un basso consumo di azoto liquido in una confezione comoda e leggera. Integrando le caratteristiche richieste dagli utenti con la più ampia varietà di tempi di tenuta e di capacità di conservazione, i contenitori criobiologici in alluminio MVE costituiscono la scelta migliore.



MVE offers the widest range of compact aluminum storage tanks available on the market today. Over the past 50 years, our product designs have improved through end-user input and evolved into a unique selection of units. The SC Series is designed for the user who has small capacity needs, but requires long-term storage and low liquid nitrogen consumption in a convenient lightweight package.

Features Include:

- Designed for large capacity storage
- Low liquid nitrogen consumption
- Convenient lightweight package

	SC 3/3	SC 8/5	SC 11/7	SC 20/20	SC 33/26	SC 36/32	Super 2
<b>Maximum Storage Capacity</b>							
Number of Canisters	6	6	6	6	6	6	6
Number of 1/2 cc Straws 10/cane	-	-	660	540	540	540	720
Number of 1/2 cc Straws 1 Level Bulk	1.122	1.122	879	780	780	780	1.122
Number of 1.2 & 2.0 ml Vials 5/cane	-	-	210	150	150	150	210
<b>Performance</b>							
LN2 Capacity L	3,6	8,4	11,0	20,5	33,0	36,5	24,5
Static Evaporation Rate* L/day	0,13	0,15	0,16	0,09	0,13	0,10	0,085
Normal Working Duration**, Full Days	17	35	43	142	182	224	180
<b>Unit Dimensions</b>							
Neck Opening in. (mm)	2,18 (55)	2,18 (55)	2,18 (55)	2,00 (51)	2,00 (51)	2,00 (51)	2,18 (55,4)
Overall Height in. (mm)	16,0 (406)	18,5 (470)	21,6 (549)	25,7 (652)	25,9 (657)	27,2 (690)	28,2 (716)
Outer Diameter in. (mm)	8,7 (222)	10,2 (260)	10,2 (260)	14,5 (368)	18,2 (464)	18,2 (464)	14,5 (368)
Canister Height in. (mm)	5,0 (127)	5,0 (127)	11,0 (279)	11,0 (279)	11,0 (279)	11,0 (279)	11,0 (279)
Canister Diameter in. (mm)	1,65 (41,9)	1,65 (41,9)	1,65 (41,9)	1,50 (38)	1,50 (38)	1,50 (38)	1,65 (41,9)
Weight Empty lb. (kg)	8 (3,6)	12 (5,3)	17 (7,7)	26 (11,8)	34 (15,4)	34 (15,4)	26,5 (12)
Weight Full lb. (kg)	14,4 (65)	27,0 (12,1)	36,6 (16,6)	62,5 (28,3)	93,4 (42,4)	100,0 (44,8)	68,4 (31)

\* Static evaporation rate and static holding time are nominal. Actual rate and holding time will be affected by the nature of container use, atmospheric conditions, and manufacturing tolerances.

\*\* Normal Working Duration is an arbitrary reference, to estimate container performance under normal operating conditions. Actual working time may vary due to current atmospheric conditions, container history, manufacturing tolerances and any individual patterns of use.